

SINGLE-PHASE INVERTERS

SUNZET SP

New single-phase on-grid string inverters range

Description



The SUNZET SP string inverters are easy operation devices that have been designed to cover the needs of all mains connected solar generation plants.. In an effort to improve the yield of solar plants, the SUNZET SP inverters offers a very high efficiency, exceeding 97%.

The SUNZET SP stands out due to its Web server application, accesible through its SNMP connection and through a WIFI connection (optional). In addition to this, the new SUNZET SP range provides a LCD display, where the customer is able to accesss all inverter information, including production data.

The SUNZET SP can work at input DC voltages between 120 to 500 VDC and it's housing has IP54 / IP65.



Sunzet SP 5 KW

Features

- > Maximum power point tracking (MPPT)
- > High energy efficiency, higher than 97%
- > Very low harmonic distortion, THD <3%
- > Direct mains connection
- > Unlimited parallel connection arrangements
- > Anti-islanding protection with automatic shut down
- > Monitoring from the unit with LCD
- > Protection against: inverse polarity, short-circuits, overvoltages, isolation failure
- > SNMP connection: Web server included
- > Range of input DC voltages (120-500 VDC)
- > Compact size, light weight, easy installation
- > WIFI connection (optional)
- > Ipad @ application (optional)
- > Built-in production log capacity (optional)
- > Remote SCADA (SWS 1000): communications system, parameter display, inverter records control, production data storage etc, (optional)

Connectivity and accessories

> Sunzet Web server integrated

PC-based Web server programme for full access to inverter data by Zigor to monitor and communicate with SUNZET SP inverters. (integrated)

> SWS 1000

The SWS 1000 Scada system is a platform for monitoring and register variables, check and modify the settings as well as customise all parameters from the SUNZET SP inverters. (optional)

See more information about connectivity and accessories on page 48

on-grid solar plants

mid voltage solar plants

hybrid generation

energy saving

telecom back up

wind energy



NON - STOP POWER

ZIGOR

ELECTRICAL CHARACTERISTICS					
Model	Sunzet SP 2	Sunzet SP 3.6	Sunzet SP 4	Sunzet SP 5	Sunzet SP 6
Reference	301203	301204	301221	200075	301205
Max. output power	2 KW	3,68 KW	4 KW	5 KW	6,6 KW
SYSTEM					
Conversion mode	High frequency PWM				
Electromechanical method	Low loss transformer (optional)				
DC INPUT					
Nominal DC voltage	360V				
Maximum DC voltage	500V				
Operating range DC	120-500V				
Operating range DC for MPPT	150-450V				
No. independent MPPT	1(14.6 A Max)	2(12.2 A Max)	2(14 A Max)	2(17.65 A Max)	2(23.4 A Max)
AC OUTPUT					
No. phases/No. wires	1- phase/2- wires or 1 – phase/ 3 – wires (LNG)				
Nominal voltage AC	230V				
Nominal frequency	50/60 Hz				
Nominal output current AC	8.7 A	16 A	17.4 A	21.7 A	28.7 A
Harmonic distortion range for nominal current	<3%				
Power factor	Over 0.99 (at nominal output current)				
Maximum efficiency	97%	97%	97,10%	97,10%	97,10%
European efficiency	96,5%	96,6%	96,6%	96,8%	96,7%
PROTECTION					
Input	Ground fault / DC isolation fault				
Output	Over-undervoltage/ Over-under frequency / Islanding				
Protection class	IP 54 / IP 65				
INTERFACE					
Standard	TCP/IP Ethernet/USB				
Optional	WIFI/RS485				
ENVIRONMENTAL CHARACTERISTICS					
Temperature	-20°C to +50°C/ -4°F to 122°F				
Relative humidity	0-90% without condensation				
Altitude	< 2000m				
MECHANICAL CHARACTERISTICS					
Dimensions mm (WxHxD)	470x525x195				
Estimated weight kg	30				
Cooling	Intelligent fan cooling				
STANDARDS					
Certificates	CE Marking				
Directives	2004/108/CE 2006/95/CE				
Standards	UNE-EN 61000-6-3, UNE-EN 61000-6-2 UNE-EN 50178 IEC 62116				
Countries standards					
USA	UL 1741				
Italy	DK5940				
Germany	VDE 0126-1-1				
England	G83/1-1				
Australia	AS				

These specifications may be changed without notice.